
RiotKit Do Documentation

Release 1

Wolnosciewicz Team

Nov 08, 2020

Contents:

1	Example use cases	3
2	Install RKD	5
3	Getting started in freshly created structure	7
4	Create your first task with Beginners guide - on YAML syntax example	9
5	Check how to use commandline to run tasks in RKD with Commandline basics	11
6	See how to import existing tasks to your Makefile with Importing tasks page	13
7	Keep learning	15
7.1	Beginners guide - on YAML syntax example	15
7.1.1	Where to place files	15
7.1.2	Environment variables	15
7.1.3	Arguments parsing	16
7.1.4	Defining tasks in Python code	16
7.1.5	YAML syntax reference	17
7.2	Extended usage - Makefile in Python syntax	18
7.2.1	Check ADVANCED usage page for description of all environment variables, mechanisms, good practices and more	20
7.3	Commandline basics	20
7.3.1	Tasks arguments usage in shell and in scripts	20
7.4	Importing tasks	21
7.4.1	1) Install a package	21
7.4.2	2) In YAML syntax	21
7.4.3	2) In Python syntax	22
7.4.4	Ready to go? Check Built-in tasks that you can import in your Makefile	22
7.5	ADVANCED usage	22
7.5.1	Troubleshooting	22
7.5.2	Loading priority	22
7.5.2.1	Environment variables loading order from .env and from .rkd	22
7.5.2.2	Environment variables loading order in YAML syntax	22
7.5.2.3	Order of loading of makefile files in same .rkd directory	23
7.5.2.4	Paths and inheritance	23
7.5.2.5	Tasks execution	23

7.5.3	Tasks development	23
7.5.3.1	Option 1) Simplest - in YAML syntax	24
7.5.3.2	Option 2) For Python developers - task as a class	25
7.5.3.3	Option 3) Quick and elastic way in Python code of Makefile.py	26
7.5.3.4	Please check Tasks API for interfaces description	27
7.5.4	Global environment variables	27
7.5.4.1	RKD_WHITELIST_GROUPS	27
7.5.4.2	RKD_ALIAS_GROUPS	27
7.5.4.3	RKD_UI	27
7.5.4.4	RKD_AUDIT_SESSION_LOG	27
7.5.4.5	RKD_BIN	28
7.5.5	Custom distribution	28
7.5.5.1	Example	28
7.5.5.2	Read more in Global environment variables	29
7.5.6	Tasks API	29
7.5.6.1	Each task must implement a TaskInterface	29
7.5.6.2	To include a task, wrap it in a declaration	31
7.5.6.3	To create an alias for task or multiple tasks	31
7.5.6.4	Execution context provides parsed shell arguments and environment variables	31
7.5.6.5	Interaction with input and output	32
7.5.6.6	Storing temporary files	33
7.5.6.7	Testing	34
7.5.7	Working with YAML files	35
7.5.7.1	YAML parsing API	35
7.5.7.2	FAQ	36
7.5.7.3	API	36
7.5.8	Creating installer wizards with RKD	36
7.5.8.1	Concept	37
7.5.8.2	Example Wizard	37
7.5.8.3	Using Wizard results internally	37
7.5.8.4	Example of loading stored values by other task	37
7.5.8.5	API	38
7.5.9	Good practices	38
7.5.9.1	Do not use os.getenv()	38
7.5.9.2	Define your environment variables	38
7.5.9.3	Use sh(), exec(), rkd() and silent_sh()	38
7.5.9.4	Do not print if you do not must, use io()	38
7.5.10	Process isolation and permissions changing with sudo	39
7.5.10.1	Mechanism	39
7.5.10.2	Permissions changing with sudo	39
7.5.10.3	Future usage	39
7.5.11	Docker entrypoints under control	39
7.5.11.1	Environment variables	39
7.5.11.2	Arguments propagation	40
7.5.11.3	Tasks customization	40
7.5.11.4	Massive files rendering with JINJA2	40
7.5.11.5	Privileges dropping	40
7.5.12	Testing with unittest	40
7.5.12.1	Example: Running a task on a fully featured RKD executor	40
7.5.12.2	Example: Mocking RKD-specific dependencies in TaskInterface	41
7.5.12.3	Documentation	41
7.6	Built-in tasks	43
7.6.1	Shell	43
7.6.1.1	:sh	43

7.6.1.2	:exec	44
7.6.1.3	Class to import: BaseShellCommandWithArgumentParsingTask	44
7.6.2	Technical/Core	45
7.6.2.1	:init	45
7.6.2.2	:tasks	45
7.6.2.3	:version	45
7.6.2.4	CallableTask	45
7.6.2.5	:rkd:create-structure	46
7.6.2.6	:file:line-in-file	48
7.6.3	Python	48
7.6.3.1	:py:publish	49
7.6.3.2	:py:build	49
7.6.3.3	:py:install	50
7.6.3.4	:py:clean	50
7.6.3.5	:py:unittest	50
7.6.4	ENV	50
7.6.4.1	:env:get	50
7.6.4.2	:env:set	51
7.6.5	JINJA	51
7.6.5.1	:j2:render	51
7.6.5.2	:j2:directory-to-directory	51

Index

RKD is a stable, open-source, multi-purpose automation tool which balance flexibility with simplicity. The primary language is Python and YAML syntax.

RiotKit-Do can be compared to **Gradle** and to **GNU Make**, by allowing both Python and Makefile-like YAML syntax.

What I can do with RKD?

- Simplify the scripts
- Put your Python and Bash scripts inside a YAML file (like in GNU Makefile)
- Do not reinvent the wheel (argument parsing, logs, error handling for example)
- Share the code across projects and organizations, use native Python Packaging to share tasks (like in Gradle)
- Natively integrate scripts with .env files
- Automatically generate documentation for your scripts
- Maintain your scripts in a good standard

RKD can be used on PRODUCTION, for development, for testing, to replace some of Bash scripts inside docker containers, and for many more, where Makefile was used.

<pre> :create-user: description: Creates an initial administrative user become: django environment: DJANGO_SETTINGS_MODULE: 'political_prisoner.settings' arguments: "--username": default: "admin" "--password": default: "admin" "--email": default: "example@example.org" steps: - echo "Hello world in Bash - first step" - #!python import django from django.db.utils import IntegrityError django.setup() from django.contrib.auth.models import User try: User.objects.create_superuser(username=ctx.get_arg('--username'), except Exception: </pre> <p style="text-align: center; font-size: 2em; opacity: 0.5;">MAKEFILE-LIKE SYNTAX</p>	<pre> class FileRendererTask(TaskInterface): """Renders a .j2 file using environment as input variable def get_name(self) -> str: return ':render' def get_group_name(self) -> str: return ':j2' def execute(self, context: ExecutionContext) -> bool: source = context.get_arg('--source') output = context.get_arg('--output') if not os.path.isfile(source): self.io().error_msg('Source file does not exist a return False if output != '-' and not os.path.isdir(os.path.dirname self.sh('mkdir -p %s' % os.path.dirname(output)) with open(source, 'rb') as f: # @todo: Support for .rkd directories in proper o tpl = Environment(loader=FileSystemLoader(['./', from string(f.read()).decode('utf-8')) </pre> <p style="text-align: center; font-size: 2em; opacity: 0.5;">PYTHON SYNTAX</p>
--	---

CHAPTER 1

Example use cases

- Docker based production environment with multiple configuration files, procedures (see: [Harbor project](#))
- Database administrator workspace (importing dumps, creating new user accounts, plugging/unplugging databases)
- Development environment (executing migrations, importing test database, splitting tests and running parallel)
- On CI (prepare project to run on eg. Jenkins or Gitlab CI) - RKD is reproducible on local computer which makes inspection easier
- Kubernetes/OKD deployment workspace (create shared YAML parts with JINJA2 between multiple environments and deploy from RKD)
- Automate things like certificate regeneration on production server, RKD can generate any application configs using JINJA2
- Installers (RKD has built-in commands for replacing lines in files, modifying .env files, asking user questions and validating answers)

CHAPTER 2

Install RKD

RiotKit-Do is delivered as a Python package that can be installed system-wide or in a virtual environment. The virtual environment installation is similar in concept to the Gradle wrapper (gradlew)

```
# 1) via PIP
pip install rkd

# 2) Create project (will create a virtual env and commit files to GIT)
rkd :rkd:create-structure --commit
```

Getting started in freshly created structure

The “Quick start” section ends up with a **.rkd** directory, a requirements.txt and setup-venv.sh

1. Use **eval \$(setup-venv.sh)** to enter shell of your project, where RKD is installed with all dependencies
2. Each time you install anything from **pip** in your project - add it to requirements.txt, you can install additional RKD tasks from pip
3. In **.rkd/makefile.yaml** you can start adding your first tasks and imports

CHAPTER 4

Create your first task with Beginners guide - on YAML syntax example

CHAPTER 5

Check how to use commandline to run tasks in RKD with Commandline
basics

CHAPTER 6

See how to import existing tasks to your Makefile with Importing tasks
page

- YAML syntax is described also in *Tasks development* section
- Writing Python code in `makefile.yaml` requires to lookup *Tasks API*
- Learn how to import installed tasks via pip - *Importing tasks*
- You can also write tasks code in pure Python and redistribute those tasks via Python's PIP - see *Tasks development*
- With RKD you can create interactive installers - check the *Creating installer wizards with RKD* section

7.1 Beginners guide - on YAML syntax example

7.1.1 Where to place files

`.rkd` directory must always exist in your project. Inside `.rkd` directory you should place your `makefile.yaml` that will contain all of the required tasks.

Just like in UNIX/Linux, and just like in Python - there is an environment variable `RKD_PATH` that allows to define multiple paths to `.rkd` directories placed in other places - for example outside of your project. This gives a flexibility and possibility to build system-wide tools installable via Python's PIP.

7.1.2 Environment variables

RKD natively reads `.env` (called also "dot-env files") at startup. You can define default environment values in `.env`, or in other `.env-some-name` files that can be included in `env_files` section of the YAML.

Scope of environment variables

`env_files` and `environment` blocks can be defined globally, which will end in including that fact in each task, second possibility is to define those blocks per task. Having both global and per-task block merges those values together and makes per-task more important.

Example

```
version: org.riotkit.rkd/yaml/v1
environment:
  PYTHONPATH: "/project"
tasks:
  :hello:
    description: Prints variables
    environment:
      SOME_VAR: "HELLO"
    steps: |
      echo "SOME_VAR is ${SOME_VAR}, PYTHONPATH is ${PYTHONPATH}"
```

7.1.3 Arguments parsing

Arguments parsing is a strong side of RKD. Each task has it's own argument parsing, it's own generated `-help` command. Python's `argparse` library is used, so Python programmers should feel like in home.

Example

```
version: org.riotkit.rkd/yaml/v1
environment:
  PYTHONPATH: "/project"
tasks:
  :hello:
    description: Prints your name
    arguments:
      "--name":
        required: true
        #option: store_true # for booleans/flags
        #default: "Unknown" # for default values
    steps: |
      echo "Hello ${ARG_NAME}"
```

```
rkd :hello --name Peter
```

7.1.4 Defining tasks in Python code

Defining tasks in Python gives wider possibilities - to access Python's libraries, better handle errors, write less tricky code. RKD has a similar concept to hashbangs in UNIX/Linux.

There are two supported hashbangs + no hashbang:

- `#!/python`
- `#!/bash`
- (just none there)

What can I do in such Python code? Everything! Import, print messages, execute shell commands, everything.

Example

```
version: org.riotkit.rkd/yaml/v1
environment:
  PYTHONPATH: "/project"
```

(continues on next page)

(continued from previous page)

```

tasks:
  :hello:
    description: Prints your name
    arguments:
      "--name":
        required: true
        #option: store_true # for booleans/flags
        #default: "Unknown" # for default values
    steps: |
      #!python
      print('Hello %s' % ctx.get_arg('--name'))

```

Special variables

- *this* - instance of current TaskInterface implementation
- *ctx* - instance of ExecutionContext

Please check *Tasks API* for those classes reference.

7.1.5 YAML syntax reference

Let's at the beginning start from analyzing an example.

```

version: org.riotkit.rkd/yaml/v1

# optional: Import tasks from Python packages
# This gives a possibility to publish tasks and share across projects, teams,
↳ organizations
imports:
  - rkt_utils.db.WaitForDatabaseTask

# optional environment section would append those variables to all tasks
# of course the tasks can overwrite those values in per-task syntax
environment:
  PYTHONPATH: "/project/src"

# optional env files loaded there would append loaded variables to all tasks
# of course the tasks can overwrite those values in per-task syntax
#env_files:
#   - .some-dotenv-file

tasks:
  :check-is-using-linux:
    description: Are you using Linux?
    # use sudo to become a other user, optional
    become: root
    steps:
      # steps can be defined as single step, or multiple steps
      # each step can be in a different language
      # each step can be a multiline string
      - "[[ $(uname -s) == \"Linux\" ]] && echo \"You are using Linux, cool\""
      - echo "step 2"
      - |
          #!python
          print('Step 3')

```

(continues on next page)

(continued from previous page)

```

:hello:
  description: Say hello
  arguments:
    "--name":
      help: "Your name"
      required: true
      #default: "Peter"
      #option: "store_true" # for booleans
  steps: |
    echo "Hello ${ARG_NAME}"

    if [[ $(uname -s) == "Linux" ]]; then
      echo "You are a Linux user"
    fi

```

imports - Imports external tasks installed via Python' PIP. That's the way to easily share code across projects

environment - Can define default values for environment variables. Environment section can be defined for all tasks, or per task

env_files - Includes .env files, can be used also per task

tasks - List of available tasks, each task has a name, description, list of steps (or a single step), arguments

Running the example:

1. Create a .rkd directory
2. Create .rkd/makefile.yaml file
3. Paste/rewrite the example into the .rkd/makefile.yaml
4. Run `rkd :tasks` from the directory where the .rkd directory is placed
5. Run defined tasks `rkd :hello :check-is-using-linux`

Example projects using Makefile YAML syntax:

- [Taiga docker image](#)
- [Taiga Events docker image](#)
- [K8S Workspace](#)

7.2 Extended usage - Makefile in Python syntax

Not only tasks can be written in Python code, but Makefile too - such makefile is called `makefile.py`, and placed in `.rkd` directory.

Example:

```

import os
from rkd.api.syntax import TaskAliasDeclaration as Task # RKD API (for defining_
↳shortcuts/aliases for whole tasks lists)
from rkd.api.syntax import TaskDeclaration # RKD API (for declaring_
↳usage of given task, importing it)
from rkd.api.contract import ExecutionContext # RKD API (one of_
↳dependencies - context gives us access to commandline arguments and environment_
↳variables)

```

(continues on next page)

(continued from previous page)

```

from rkd_python import imports as PythonImports           # group of imports (not all
↳packages supports it, but most of them)
from rkd.standardlib.jinja import FileRendererTask      # single task
from rkd.standardlib import CallableTask                # Basic Python callable task
↳for a little bit advanced usage
# from .mypackage import MyTask                         # import your task from
↳local package

def example_method(ctx: ExecutionContext, task: CallableTask) -> bool:
    os.system('xdg-open https://twitter.com/wrkclasshistory')
    return True

IMPORTS = [
    # We declare that we will use this task.
    # Declaration can take some additional arguments like args= or env=, to always
↳append environment and/or commandline switches
    # regardless of if user used it
    TaskDeclaration(FileRendererTask()),
    # remember about the ", " between tasks, it's an array/list ;)
    # TaskDeclaration(MyTask())

    TaskDeclaration(CallableTask(':read-real-history', example_method, description=
↳'Example task with simple Python code'))
]

IMPORTS += PythonImports()

TASKS = [
    # declared task-aliases. A Task Alias is a shortcut eg. ":release" that will
↳expands to ":py:build :py:publish --username= (...)"
    # the best feature in task-aliases is that you can append and overwrite last
↳commandline arguments, those will be added
    # at the end of the command
    Task(':release', description='Release to PyPI (snapshot when on master, release
↳on tag)',
    to_execute=[
        ':py:build', ':py:publish', '--username=__token__', '--password=${PYPI_
↳TOKEN}'
    ]),

    Task(':test', [':py:unittest'], description='Run unit tests'),
    Task(':docs', [':sh', '-c', ''' set -x
        cd docs
        rm -rf build
        sphinx-build -M html "source" "build"
        '''])
]

```

- The Python syntax is very flexible
- You can create your own local packages and import them here, create own advanced structure
- Possibility to declare aliases and adjust TaskDeclarations for advanced usage (YAML syntax does not offer this)

Example projects using Makefile.py syntax:

- [TunMan](#)

- RiotKit Harbor building scripts
- RiotKit CI Utils

7.2.1 Check **ADVANCED** usage page for description of all environment variables, mechanisms, good practices and more

7.3 Commandline basics

RKD command-line usage is highly inspired by GNU Make and Gradle, but it has its own extended possibilities to make your scripts smaller and more readable.

- Tasks are prefixed always with “:”.
- Each task can handle it’s own arguments (unique in RKD)
- “@” allows to propagate arguments to next tasks (unique in RKD)

7.3.1 Tasks arguments usage in shell and in scripts

Executing multiple tasks in one command:

```
rkd :task1 :task2
```

Multiple tasks with different switches:

```
rkd :task1 --hello :task2 --world --become=root
```

Second task will run as root user, additionally with `--world` parameter.

Tasks sharing the same switches

Both tasks will receive switch “--hello”

```
# expands to:
# :task1 --hello
# :task2 --hello
rkd @ --hello :task1 :task2

# handy, huh?
```

Advanced usage of shared switches

Operator “@” can set switches anytime, it can also clear or replace switches in **NEXT TASKS**.

```
# expands to:
# :task1 --hello
# :task2 --hello
# :task3
# :task4 --world
# :task5 --world
rkd @ --hello :task1 :task2 @ :task3 @ --world :task4 :task5
```

Written as a pipeline (regular bash syntax)

It’s exactly the same example as above, but written multiline. It’s recommended to write multiline commands if they are longer.

```
rkd @ --hello \
:task1 \
:task2 \
@
:task3 \
@ --world \
:task4 \
:task5
```

7.4 Importing tasks

Tasks can be defined as installable Python’s packages that you can import in your Makefile

Please note:

- To import a group, the package you try to import need to hvve a defined **imports()** method inside of the package.
- The imported group does not need to import automatically dependend tasks (but it can, it is recommended), you need to read into the docs of specific package if it does so

7.4.1 1) Install a package

RKD defines dependencies using Python standards.

Example: Given we want to import tasks from package “rkt_armutils”.

```
echo "rkt_armutils==3.0" >> requirements.txt
pip install -r requirements.txt
```

Good practices:

- Use fixed versions eg. 3.0 or even 3.0.0 and upgrade only intentionally to reduce your work. Automatic updates, especially of major versions

could be unpredictable and possibly can break something time-to-time

How do I check latest version?:

- Simply install a package eg. `pip install rkt_armutils`, then do a `pip show rkt_armutils` and write the version

to the requirements.txt, or lookup a package first at https://pypi.org/project/rkt_armutils/ (where rkt_armutils is an example package)

7.4.2 2) In YAML syntax

Example: Given we want to import task “InjectQEMUBinaryIntoContainerTask”, or we want to import whole “rkt_armutils.docker” group

```
imports:
  # Import whole package, if the package defines a group import (method imports())
  - rkt_armutils.docker

  # Or import single task
  - rkt_armutils.docker.InjectQEMUBinaryIntoContainerTask
```

7.4.3 2) In Python syntax

Example: Given we want to import task “InjectQEMUBinaryIntoContainerTask”, or we want to import whole “rkt_armutils.docker” group

```
from rkd.api.syntax import TaskDeclaration
from rkt_armutils.docker import InjectQEMUBinaryIntoContainerTask

# ... (use "+" operator to append, remove "+" if you didn't define any import yet)
IMPORTS += [TaskDeclaration(InjectQEMUBinaryIntoContainerTask)]
```

7.4.4 Ready to go? Check Built-in tasks that you can import in your Makefile

7.5 ADVANCED usage

7.5.1 Troubleshooting

1. Output is corrupted or there is no output from a shell command executed inside of a task

The output capturing is under testing. The Python’s subprocess module is skipping “sys.stdout” and “sys.stderr” by writing directly to /dev/stdout and /dev/stderr, which makes output capturing difficult.

Run rkd in compat mode to turn off output capturing from shell commands:

```
RKD_COMPAT_SUBPROCESS=true rkd :some-task-here
```

7.5.2 Loading priority

7.5.2.1 Environment variables loading order from .env and from .rkd

Legend: Top is most important, the variables loaded on higher level are not overridden by lower level

1. Operating system environment
2. Current working directory .env file
3. .env files from directories defined in RKD_PATH

7.5.2.2 Environment variables loading order in YAML syntax

Legend: Top - is most important

1. Operating system environment
2. .env file
3. Per-task “environment” section
4. Per-task “env_file” imports
5. Global “environment” section
6. Global “env_file” imports

7.5.2.3 Order of loading of makefile files in same .rkd directory

Legend: Lower has higher priority (next is appending changes to previous)

1. *.py
2. *.yaml
3. *.yml

7.5.2.4 Paths and inheritance

RKD by default search for .rkd directory in current execution directory - *./rkd*.

The search order is following (from lower to higher load priority):

1. RKD's internals (we provide a standard tasks like *:tasks*, *:init*, *:sh*, *:exec* and more)
2. */usr/lib/rkd*
3. User's home *~/rkd*
4. Current directory *./rkd*
5. *RKD_PATH*

Custom path defined via environment variable

RKD_PATH allows to define multiple paths that would be considered in priority.

```
export RKD_PATH="/some/path:/some/other/path:/home/user/riotkit/.rkd-second"
```

How the makefiles are loaded?

Each makefile is loaded in order, next makefile can override tasks of previous. That's why we at first load internals, then your tasks.

7.5.2.5 Tasks execution

Tasks are executed one-by-one as they are specified in commandline or in TaskAlias declaration (commandline arguments).

```
rkd :task-1 :task-2 :task-3
```

1. task-1
2. task-2
3. task-3

A *-keep-going* can be specified after given task eg. *:task-2 -keep-going*, to ignore a single task failure and in consequence allow to go to the next task regardless of result.

7.5.3 Tasks development

RKD has multiple approaches to define a task. The first one is simpler - in makefile in YAML or in Python. The second one is a set of tasks as a Python package.

7.5.3.1 Option 1) Simplest - in YAML syntax

Definitely the simplest way to define a task is to use YAML syntax, it is recommended for beginning users.

Example 1:

```
version: org.riotkit.rkd/yaml/v1
imports:
  - rkd.standardlib.jinja.RenderDirectoryTask

tasks:
  # see this task in "rkd :tasks"
  # run with "rkd :examples:bash-test"
  :examples:bash-test:
    description: Execute an example command in bash - show only python related tasks
    steps: |
      echo "RKD_DEPTH: ${RKD_DEPTH} # >= 2 means we are running rkd-in-rkd"
      echo "RKD_PATH: ${RKD_PATH}"
      rkd --silent :tasks | grep ":py"

  # try "rkd :examples:arguments-test --text=Hello --test-boolean"
  :examples:arguments-test:
    description: Show example usage of arguments in Bash
    arguments:
      "--text":
        help: "Adds text message"
        required: True
      "--test-boolean":
        help: "Example of a boolean flag"
        action: store_true # or store_false

    steps:
      - |
        #!bash
        echo " ==> In Bash"
        echo " Text: ${ARG_TEXT}"
        echo " Boolean test: ${ARG_TEST_BOOLEAN}"
      - |
        #!python
        print(' ==> In Python')
        print(' Text: %s ' % ctx.args['text'])
        print(' Text: %s ' % str(ctx.args['test_boolean']))
        return True

  # run with "rkd :examples:list-standardlib-modules"
  :examples:list-standardlib-modules:
    description: List all modules in the standardlib
    steps:
      - |
        #!python
        ctx: ExecutionContext
        this: TaskInterface

        import os

        print('Hello world')
        print(os)
        print(ctx)
        print(this)
```

(continues on next page)

(continued from previous page)

```
return True
```

Example 2:

```
version: org.riotkit.rkd/yaml/v1

environment:
  GLOBALLY_DEFINED: "16 May 1966, seamen across the UK walked out on a nationwide_
↳strike for the first time in half a century. Holding solid for seven weeks, they_
↳won a reduction in working hours from 56 to 48 per week "

```

Explanation of examples:

1. “arguments” is an optional dict of arguments, key is the argument name, subkeys are passed directly to argparse
2. “steps” is a mandatory list or text with step definition in Bash or Python language
3. “description” is an optional text field that puts a description visible in “:tasks” task
4. “environment” is a dict of environment variables that can be defined
5. “env_files” is a list of paths to .env files that should be included
6. “imports” imports a Python package that contains tasks to be used in the makefile and in shell usage

7.5.3.2 Option 2) For Python developers - task as a class

This way allows to create tasks in a structure of a Python module. Such task can be packaged, then published to eg. PyPI (or other private repository) and used in multiple projects.

Each task should implement methods of **rkd.api.contract.TaskInterface** interface, that’s the basic rule.

Following example task could be imported with path **rkd.standardlib.ShellCommandTask**, in your own task you would have a different package name instead of **rkd.standardlib**.

Example task from RKD standardlib:

```

class ShellCommandTask(TaskInterface):
    """Executes shell scripts"""

    def get_name(self) -> str:
        return ':sh'

    def get_group_name(self) -> str:
        return ''

    def configure_argparse(self, parser: ArgumentParser):
        parser.add_argument('--cmd', '-c', help='Shell command', required=True)

    def execute(self, context: ExecutionContext) -> bool:
        # self.sh() and self.io() are part of TaskUtilities via TaskInterface

        try:
            self.sh(context.get_arg('cmd'), capture=False)
        except CalledProcessError as e:
            self.io().error_msg(str(e))
            return False

        return True

```

Explanation of example:

1. The docstring in Python class is what will be shown in **:tasks as description**. You can also define your description by implementing **def get_description() -> str**
2. Name and group name defines a full name eg. :your-project:build
3. **def configure_argparse()** allows to inject arguments, and `-help` description for a task - it's a standard Python's argparse object to use
4. **def execute()** provides a context of execution, please read *Tasks API* chapter about it. In short words you can get commandline arguments, environment variables there.
5. **self.io()** is providing input-output interaction, please use it instead of print, please read *Tasks API* chapter about it.

7.5.3.3 Option 3) Quick and elastic way in Python code of Makefile.py

Multiple Makefile files can be used at one time, you don't have to choose between YAML and Python. This opens a possibility to define more advanced tasks in pure Python, while you have most of the tasks in YAML. It's elastic - use YAML, or Python or both.

Let's define then a task in Python in a simplest method.

Makefile.py

```

import os
from rkd.api.syntax import TaskDeclaration
from rkd.api.contract import ExecutionContext
from rkd.standardlib import CallableTask

def union_method(context: ExecutionContext) -> bool:
    os.system('xdg-open https://iwa-ait.org')
    return True

```

(continues on next page)

(continued from previous page)

```

IMPORTS = [
    # just declare a task with a name + code as function! Yay, simple!
    TaskDeclaration(CallableTask(':create-union', union_method))
]

TASKS = []

```

Extended usage - Makefile in Python syntax.

7.5.3.4 Please check Tasks API for interfaces description

7.5.4 Global environment variables

Global switches designed to customize RKD per project. Put environment variables into your **.env** file, so you will not have to prepend them in the commandline every time.

Read also about *Environment variables loading order from .env and from .rkd*

7.5.4.1 RKD_WHITELIST_GROUPS

Allows to show only selected groups in the “:tasks” list. All tasks from hidden groups are still callable.

Examples:

```

RKD_WHITELIST_GROUPS=:rkd, rkd :tasks
RKD_WHITELIST_GROUPS=:rkd rkd :tasks

```

7.5.4.2 RKD_ALIAS_GROUPS

Alias group names, so it can be shorter, or even group names could be not typed at all.

Notice: :tasks will rename a group with a first defined alias for this group

Examples:

```

RKD_ALIAS_GROUPS=":rkd->r" rkd :tasks :r:create-structure
RKD_ALIAS_GROUPS=":rkd->" rkd :tasks :create-structure

```

7.5.4.3 RKD_UI

Allows to toggle (true/false) the UI - messages like “Executing task X” or “Task finished”, leaving only tasks stdout, stderr and logs.

7.5.4.4 RKD_AUDIT_SESSION_LOG

Logs output of each executed task, when set to “true”.

Example structure of logs:

```

# ls .rkd/logs/2020-06-11/11\:06\:02.068556/
task-1-init.log task-2-harbor_service_list.log

```

7.5.4.5 RKD_BIN

Defines a command that invokes RKD eg. `rkd`. When a custom distribution is present, then this value can differ. For example project RiotKit Harbor has it's own command `harbor`, which is based on RKD, so the `RKD_BIN=harbor` would be defined in such project.

`RKD_BIN` is automatically generated, when executing task in a separate process, but it can be also set globally.

7.5.5 Custom distribution

RiotKit Do can be used as a transparent framework for writing tasks for various usage, especially for specialized usage. To simplify usage for end-user RKD allows to create a custom distribution.

Custom distribution allows to:

- Define custom 'binary' name eg. "harbor" instead of "rkd"
- Hide unnecessary tasks in custom 'binary' (filter by groups - whitelist)
- Make shortcuts to tasks: Skip writing group name, make a group name to be appended by default

7.5.5.1 Example

```
import os
from rkd import main as rkd_main

def env_or_default(env_name: str, default: str):
    return os.environ[env_name] if env_name in os.environ else default

def main():
    os.environ['RKD_WHITELIST_GROUPS'] = env_or_default('RKD_WHITELIST_GROUPS', ':env,
↳:harbor,')
    os.environ['RKD_ALIAS_GROUPS'] = env_or_default('RKD_ALIAS_GROUPS', '->:harbor')
    os.environ['RKD_UI'] = env_or_default('RKD_UI', 'false')
    rkd_main()

if __name__ == '__main__':
    main()
```

```
$ harbor :tasks
[global]
:sh # Executes shell scripts
:exec # Spawns a shell process
:init # :init task is executing ALWAYS.↳
↳That's a technical, core task.
:tasks # Lists all enabled tasks
:version # Shows version of RKD and of all↳
↳loaded tasks

[harbor]
:compose:ps # List all containers
:start # Create and start containers
:stop # Stop running containers
:remove # Forcibly stop running containers↳
↳and remove (keeps volumes)
```

(continues on next page)

(continued from previous page)

```

:service:list # Lists all defined containers in_
↳YAML files (can be limited by --profile selector)
:service:up # Starts a single service
:service:down # Brings down the service without_
↳deleting the container
:service:rm # Stops and removes a container and_
↳it's images
:pull # Pull images specified in_
↳containers definitions
:restart # Restart running containers
:config:list # Gets environment variable value
:config:enable # Enable a configuration file - YAML
:config:disable # Disable a configuration file -_
↳YAML
:prod:gateway:reload # Reload gateway, regenerate_
↳missing SSL certificates
:prod:gateway:ssl:status # Show status of SSL certificates
:prod:gateway:ssl:regenerate # Regenerate all certificates with_
↳force
:prod:maintenance:on # Turn on the maintenance mode
:prod:maintenance:off # Turn on the maintenance mode
:git:apps:update # Fetch a git repository from the_
↳remote
:git:apps:update-all # List GIT repositories
:git:apps:set-permissions # Make sure that the application_
↳would be able to write to allowed directories (eg. upload directories)
:git:apps:list # List GIT repositories

[env]
:env:get # Gets environment variable value
:env:set # Sets environment variable in the .
↳env file

Use --help to see task environment variables and switches, eg. rkd :sh --help, rkd --
↳help

```

Notices for above example:

- No need to type eg. :harbor:config:list - just :config:list (RKD_ALIAS_GROUPS used)
- No “rkd” group is displayed (RKD_WHITELIST_GROUPS used)
- There is no information about task name (RKD_UI used)

7.5.5.2 Read more in Global environment variables**7.5.6 Tasks API****7.5.6.1 Each task must implement a TaskInterface**

```
class rkd.api.contract.TaskInterface
```

```

configure_argparse (parser: argparse.ArgumentParser)
    Allows a task to configure ArgumentParser (argparse)

```

copy_internal_dependencies (*task*)

Allows to execute a task-in-task, by copying dependent services from one task to other task

exec (*cmd: str, capture: bool = False, background: bool = False*) → Optional[str]

Starts a process in shell. Throws exception on error. To capture output set capture=True

NOTICE: Use instead of subprocess. Raw subprocess is less supported and output from raw subprocess
may be not catch properly into the logs

execute (*context: rkd.api.contract.ExecutionContext*) → bool

Executes a task. True/False should be returned as return

format_task_name (*name: str*) → str

Allows to add a fancy formatting to the task name, when the task is displayed eg. on the :tasks list

get_become_as () → str

User name in UNIX/Linux system, optional. When defined, then current task will be executed as this user
(WARNING: a forked process would be started)

get_declared_envs () → Dict[str, Union[str, rkd.api.contract.ArgumentEnv]]

Dictionary of allowed envs to override: KEY -> DEFAULT VALUE

get_full_name ()

Returns task full name, including group name

get_group_name () → str

Group name where the task belongs eg. “:publishing”, can be empty.

get_name () → str

Task name eg. “:sh”

io () → rkd.api.inputoutput.IO

Gives access to Input/Output object

py (*code: str = "", become: str = None, capture: bool = False, script_path: str = None, arguments: str = ""*) → Optional[str]

Executes a Python code in a separate process

NOTICE: Use instead of subprocess. Raw subprocess is less supported and output from raw subprocess
may be not catch properly into the logs

rkd (*args: list, verbose: bool = False, capture: bool = False*) → str

Spawns an RKD subprocess

NOTICE: Use instead of subprocess. Raw subprocess is less supported and output from raw subprocess
may be not catch properly into the logs

sh (*cmd: str, capture: bool = False, verbose: bool = False, strict: bool = True, env: dict = None*) → Optional[str]

Executes a shell script in bash. Throws exception on error. To capture output set capture=True

NOTICE: Use instead of subprocess. Raw subprocess is less supported and output from raw subprocess
may be not catch properly into the logs

should_fork () → bool

Decides if task should be ran in a separate Python process (be careful with it)

silent_sh (*cmd: str, verbose: bool = False, strict: bool = True, env: dict = None*) → bool

sh() shortcut that catches errors and displays using IO().error_msg()

NOTICE: Use instead of subprocess. Raw subprocess is less supported and output from raw subprocess
may be not catch properly into the logs

```
static table (header: list, body: list, tablefmt: str = 'simple', floatfmt: str = 'g', numalign: str = 'decimal', stralign: str = 'left', missingval: str = "", showindex: str = 'default', disable_numparse: bool = False, colalign: str = None)
```

Renders a table

Parameters

- **header** –
- **body** –
- **tablefmt** –
- **floatfmt** –
- **numalign** –
- **stralign** –
- **missingval** –
- **showindex** –
- **disable_numparse** –
- **colalign** –

Returns Formatted table as string

7.5.6.2 To include a task, wrap it in a declaration

```
class rkd.api.syntax.TaskDeclaration (task: rkd.api.contract.TaskInterface, env: Dict[str, str] = {}, args: List[str] = [])
```

7.5.6.3 To create an alias for task or multiple tasks

```
class rkd.api.syntax.TaskAliasDeclaration (name: str, to_execute: List[str], env: Dict[str, str] = {}, description: str = "")
```

Allows to define a custom task name that triggers other tasks in proper order

7.5.6.4 Execution context provides parsed shell arguments and environment variables

```
class rkd.api.contract.ExecutionContext (declaration: rkd.api.contract.TaskDeclarationInterface, parent: Optional[rkd.api.contract.GroupDeclarationInterface] = None, args: Dict[str, str] = {}, env: Dict[str, str] = {}, defined_args: Dict[str, dict] = {})
```

Defines which objects could be accessed by Task. It's a scope of a single task execution.

```
get_arg (name: str) → Optional[str]
```

Get argument or option

Usage: `ctx.get_arg('-name')` # for options `ctx.get_arg('name')` # for arguments

Raises `KeyError` when argument/option was not defined

Returns Actual value or default value

```
get_arg_or_env (name: str) → Optional[str]
```

Provides value of user input

Usage: `get_arg_or_env('-file-path')` resolves into `FILE_PATH` env variable, and `-file-path` switch (`file_path` in `argparse`)

Behavior: When user provided explicitly switch eg. `-history-id`, then it's value will be taken in priority. If switch `-history-id` was not used, but user provided `HISTORY_ID` environment variable, then it will be considered.

If no switch provided and no environment variable provided, but a switch has default value - it would be returned.

If no switch provided and no environment variable provided, the switch does not have default, but environment variable has a default value defined, it would be returned.

When the `-switch` has default value (user does not use it, or user sets it explicitly to default value), and environment variable `SWITCH` is defined, then environment variable would be taken.

From RKD 2.1 the environment variable names can be mapped to any `ArgParse` switch.

Below example maps "COMMAND" environment variable to "-cmd" switch.

Raises `MissingInputException` - When no switch and no environment variable was provided, then an exception is thrown.

get_env (*name: str, switch: str = "", error_on_not_used: bool = False*)
Get environment variable value

7.5.6.5 Interaction with input and output

class `rkd.api.inputoutput.IO`

Interacting with input and output - stdout/stderr/stdin, logging

capture_descriptors (*target_files: List[str] = None, stream=None, enable_standard_out: bool = True*)

Capture stdout and stderr from a block of code - use with 'with'

critical (*text*)

Logger: critical

debug (*text*)

Logger: debug

err (*text*)

Standard error

errln (*text*)

Standard error + newline

error (*text*)

Logger: error

error_msg (*text*)

Error message (optional output)

h1 (*text*)

Heading #1 (optional output)

h2 (*text*)

Heading #2 (optional output)

h3 (*text*)

Heading #3 (optional output)

h4 (*text*)
 Heading #3 (optional output)

info (*text*)
 Logger: info

info_msg (*text*)
 Informational message (optional output)

is_silent () → bool
 Is output silent? In silent mode OPTIONAL MESSAGES are not shown

opt_out (*text*)
 Optional output - fancy output skipped in `-silent` mode

opt_outln (*text*)
 Optional output - fancy output skipped in `-silent` mode + newline

out (*text*)
 Standard output

outln (*text*)
 Standard output + newline

print_group (*text*)
 Prints a colored text inside brackets [text] (optional output)

print_line ()
 Prints a newline

print_opt_line ()
 Prints a newline (optional output)

print_separator ()
 Prints a text separator (optional output)

success_msg (*text*)
 Success message (optional output)

warn (*text*)
 Logger: warn

7.5.6.6 Storing temporary files

class `rkd.api.temp.TempManager` (*chdir: str = './rkd'*)
 Manages temporary files inside `.rkd` directory Using this class you make sure your code is more safe to use on Continuous Integration systems (CI)

Usage: `path = self.temp.assign_temporary_file(mode=0o755)`

assign_temporary_file (*mode: int = 493*) → str
 Assign a path for writing temporary files in RKD workspace

Note: The RKD is executing the `finally_clean_up()` at the end of each task

Usage:

```

try: path = RKDTemp.assign_temporary_file_path() # (...) some action there
finally: RKDTemp.finally_clean_up()

```

finally_clean_up()

Used to clean up all temporary files at the end of the code execution

TaskExecutor is running this method after each finished task

7.5.6.7 Testing

class `rkd.api.testing.BasicTestingCase` (*methodName='runTest'*)

Provides minimum of:

- Doing backup of environment and cwd
- Methods for mocking task dependencies (RKD-specific like ExecutionContext)

environment (*environ: dict*)

Mocks environment

Example usage:

```
with self.environment({'RKD_PATH': SCRIPT_DIR_PATH + '/../docs/examples/env-in-yaml/rkd'}):  
    ...
```

Parameters environ –

Returns

static `mock_execution_context` (*task: rkd.api.contract.TaskInterface, args: Dict[str, str] = None, env: Dict[str, str] = None, defined_args: Dict[str, dict] = None*) → `rkd.api.contract.ExecutionContext`

Prepares a simplified `rkd.api.contract.ExecutionContext` instance

Parameters

- **task** –
- **args** –
- **env** –
- **defined_args** –

Returns

static `satisfy_task_dependencies` (*task: rkd.api.contract.TaskInterface, io: rkd.api.inputoutput.IO = None*) → `rkd.api.contract.TaskInterface`

Inserts required dependencies to your task that implements `rkd.api.contract.TaskInterface`

Parameters

- **task** –
- **io** –

Returns

setUp() → None

Hook method for setting up the test fixture before exercising it.

tearDown() → None

Hook method for deconstructing the test fixture after testing it.

class `rkd.api.testing.FunctionalTestingCase` (*methodName='runTest'*)

Provides methods for running RKD task or multiple tasks with output and exit code capturing. Inherits `OutputCapturingSafeTestCase`.

execute_mocked_task_and_get_output (*task: rkd.api.contract.TaskInterface, args=None, env=None*) → str

Run a single task, capturing it's output in a simplified way. There is no whole RKD bootstrapped in this operation.

Parameters

- **task** (`TaskInterface`) –
- **args** (`dict`) –
- **env** (`dict`) –

Returns

run_and_capture_output (*argv: list, verbose: bool = False*) → Tuple[str, int]

Run task(s) and capture output + exit code. Whole RKD from scratch will be bootstrapped there.

Example usage: `full_output, exit_code = self.run_and_capture_output([':tasks'])`

Parameters

- **argv** (`list`) – List of tasks, arguments, commandline switches
- **verbose** (`bool`) – Print all output also to stdout

Returns

class `rkd.api.testing.OutputCapturingSafeTestCase` (*methodName='runTest'*)

Provides hooks for keeping stdout/stderr immutable between tests.

setUp () → None

Hook method for setting up the test fixture before exercising it.

tearDown () → None

Hook method for deconstructing the test fixture after testing it.

7.5.7 Working with YAML files

`Makefile.yaml` has checked syntax before it is parsed by RKD. A `jsonschema` library was used to validate YAML files against a JSON formatted schema file.

This gives the early validation of typing inside of YAML files, and a clear message to the user about place where the typo is.

7.5.7.1 YAML parsing API

Schema validation is a part of YAML parsing, the preferred way of working with YAML files is to not only parse the schema but also validate. In result of this there is a class that wraps `yaml` library - `rkd.yaml_parser.YamlFileLoader`, use it instead of plain `yaml` library.

Notice: The YAML and schema files are automatically searched in `.rkd`, `.rkd/schema` directories, including `RKD_PATH`

Example usage:

```
from rkd.yaml_parser import YamlFileLoader

parsed = YamlFileLoader([]).load_from_file('deployment.yml', 'org.riotkit.harbor/
↳deployment/v1')
```

7.5.7.2 FAQ

1. *FileNotFoundError: Schema “my-schema-name.json” cannot be found, looked in: [‘../riotkit-harbor’, ‘../riotkit-harbor/schema’, ‘../riotkit-harbor/rkd/schema’, ‘/home/.../rkd/schema’, ‘usr/lib/rkd/schema’, ‘usr/lib/python3.8/site-packages/rkd/internal/schema’]*

The schema file cannot be found, the name is invalid or file missing. The schema should be placed somewhere in the .rkd/schema directory - in global, in home directory or in project.

2. *rkd.exception.YAMLFileValidationError: YAML schema validation failed at path “tasks” with error: [] is not of type ‘object’*

It means you created a list (starts with “-“) instead of dictionary at “tasks” path.

Example what went wrong:

```
tasks:
  - description: first
  - description: second
```

Example how it should be as an ‘object’:

```
tasks:
  first:
    description: first

  second:
    description: second
```

7.5.7.3 API

class `rkd.yaml_parser.YamlFileLoader` (*paths: List[str]*)

YAML loader extended by schema validation support

YAML schema is stored as JSON files in .rkd/schema directories. The Loader looks in all paths defined in RKD_PATH as well as in paths provided by ApplicationContext

find_path_by_name (*filename: str, subdir: str*) → str

Find schema in one of RKD directories or in current path

load (*stream, schema_name: str*)

Loads a YAML, validates and return parsed as dict/list

load_from_file (*filename: str, schema_name: str*)

Loads a YAML file from given path, a wrapper to load()

7.5.8 Creating installer wizards with RKD

Wizard is a component designed to create comfortable installers, where user has to answer a few questions to get the task done.

7.5.8.1 Concept

- User answers questions invoked by `ask()` method calls
- At the end the `finish()` is called, which acts as a commit, saves answers into `.rkd/tmp-wizard.json` by default and into the `.env` file (depends on if `to_env=true` was specified)
- Next RKD task executed can read `.rkd/tmp-wizard.json` looking for answers, the answers placed in `.env` are already loaded automatically as part of standard mechanism of environment variables support

7.5.8.2 Example Wizard

```
from rkd.api.inputoutput import Wizard

# self is the TaskInterface instance, in Makefile.yaml it would be "this", in Python_
↳code it is "self"
Wizard(self)\
    .ask('Service name', attribute='service_name', regexp='([A-Za-z0-9_]+)', default=
↳'redis')\
    .finish()
```

```
Service name [[A-Za-z0-9_+]] [default: redis]:
-> redis
```

Example of application that is using Wizard to ask interactive questions

7.5.8.3 Using Wizard results internally

Wizard is designed to keep the data on the disk, so you can access it in any other task executed, but this is not mandatory. You can skip committing changes to disk by not using `finish()` which is **flushing data to json and to .env files**.

Use `wizard.answers` to see all answers that would be put into json file, and `wizard.to_env` to browse all environment variables that would be set in `.env` if `finish()` would be used.

7.5.8.4 Example of loading stored values by other task

Wizard stores values into file and into `.env` file, so it can read it from file after it was stored there. This allows you to separate Wizard questions into one RKD task, and the rest of logic/steps into other RKD tasks.

```
from rkd.api.inputoutput import Wizard

# ... assuming that previously the Wizard was completed by user and the finish()_
↳method was called ...

wizard = Wizard(self)
wizard.load_previously_stored_values()

print(wizard.answers, wizard.to_env)
```

7.5.8.5 API

```
class rkd.api.inputoutput.Wizard (task: TaskInterface, filename: str = 'tmp-wizard.json')

    ask (title: str, attribute: str, regexp: str = "", to_env: bool = False, default: str = None, choices: list = [],
        secret: bool = False) → rkd.api.inputoutput.Wizard
        Asks user a question

    Usage: wizard = Wizard(self) wizard.ask('In which year the Spanish social revolution has begun?',
        attribute='year', choices=['1936', '1910'])
        wizard.finish()

    finish () → rkd.api.inputoutput.Wizard
        Commit all pending changes into json and .env files

    input (secret: bool = False)
        Extracted for unit testing to be possible easier

    load_previously_stored_values ()
        Load previously saved values
```

7.5.9 Good practices

7.5.9.1 Do not use os.getenv()

Note: Only in Python code

The ExecutionContext is providing processed environment variables. Variables could be overridden on some levels eg. in makefile.py - rkd.api.syntax.TaskAliasDeclaration can take a dict of environment variables to force override.

Use `context.get_env()` instead.

7.5.9.2 Define your environment variables

Note: Only in Python code

By using `context.get_env()` you are enforced to implement a `TaskInterface.get_declared_envs()` returning a list of all environment variables used in your task code.

All defined environment variables will land in `-help`, which is considered as a task self-documentation.

7.5.9.3 Use sh(), exec(), rkd() and silent_sh()

Using raw `subprocess` will make your commands output invisible in logs, as the subprocess is writing directly to `stdout/stderr` skipping `sys.stdout` and `sys.stderr`. The methods provided by RKD are buffering the output and making it possible to save to both file and to console.

7.5.9.4 Do not print if you do not must, use io()

`rkd.api.inputoutput.IO` provides a standardized way of printing messages. The class itself distinct importance of messages, writing them to proper `stdout/stderr` and to log files.

`print` is also captured by IO, but should be used only eventually.

7.5.10 Process isolation and permissions changing with sudo

Alternatively called “forking” is a feature of RKD similar to Gradle’s JVM forking - the task can be run in a separate Python’s process. This gives a possibility to run specific task as a specific user (eg. upgrade permissions to ROOT or downgrade to regular user)

7.5.10.1 Mechanism

RKD uses serialization to transfer data between processes - a standard `pickle` library is used. Pickle has limitations on what can be serialized - any inner-methods and lambdas cannot be returned by task.

To test if your task is compatible with running as a separate process simply add `--become=USER-NAME` to the commandline of your task. If it will fail due to serialization issue, then you will be notified with a nice `stacktrace`.

Technically the mechanism works on the task executor level, it means that process isolation is independent of the programming language as whole task’s `execute()` is ran in a separate process, even if task is declared in YAML and has Bash steps.

7.5.10.2 Permissions changing with sudo

YAML syntax allows to define additional attribute `become`, that if defined then makes whole task to execute inside a separate Python process ran with `sudo`.

Additionally the RKD commandline supports a per-task parameter `--become`

7.5.10.3 Future usage

The mechanism is universal, it can be possibly used to sandbox, or even to execute tasks remotely. Currently we do not support such features but we do not say its impossible in the future.

7.5.11 Docker entrypoints under control

RKD has enough small footprint so that it can be used as an endpoint in docker containers. There are a few features that are making RKD very attractive to use in this role.

7.5.11.1 Environment variables

Defined commandline `--my-switch` can have optionally overridden value with environment variable. In docker it can help easily adjusting default values.

Task needs to create an explicit declaration of environment variable:

```
def get_declared_envs(self) -> Dict[str, ArgumentEnv]:
    return {
        'MY_SWITCH': ArgumentEnv(name='MY_SWITCH', switch='--switch-name', default='
↵'),
    }
```

```
def execute(self, ctx: ExecutionContext) -> bool:
    # this one will look for a switch value, if switch has default value, then it_
↵will look for an environment variable
    ctx.get_arg_or_env('--my-switch')
```

7.5.11.2 Arguments propagation

When setting `ENTRYPOINT ["rkd", ":entrypoint"]` everything that will be passed as docker's CMD will be passed to rkd, so additional tasks and arguments can be appended.

7.5.11.3 Tasks customization

It is a good practice to split your entrypoint into multiple tasks executed one-by-one. This gives you a possibility to create new `makefile.yaml/py` in any place and modify `RKD_PATH` environment variable to add additional tasks or replace existing. The `RKD_PATH` has always higher priority than current `.rkd` directory.

Possible options:

- Create a bind-mount volume with additional `.rkd/makefile.yaml`, add `.rkd/makefile.yaml` into container and set `RKD_PATH` to point to `.rkd` directory
- Create new docker image having original in `FROM`, add `.rkd/makefile.yaml` into container and set `RKD_PATH` to point to `.rkd` directory

7.5.11.4 Massive files rendering with JINJA2

`:j2:directory-to-directory` is a specially designed task to render JINJA2 templates recursively preserving a directory structure. You can create for example `templates/etc/nginx/nginx.conf.j2` and render `./templates/etc` into `/etc` with all files being copied on the fly.

All jinja2 templates will have access to environment variables - with templating syntax you can define very advanced configuration files

7.5.11.5 Privileges dropping

Often in entrypoint there are cache/uploads permissions corrected, so the `root` user is used. To migrate the application, to run the webserver the privileges could be dropped.

Solutions:

- In YAML syntax each task have a possible field to use: `become: user-name-here`
- In Python class `TaskInterface` has method `get_become_as()` that should return empty string or a username to use `sudo` with
- In commandline there is a switch `--become=user-name-here` that can be used with most of the tasks

7.5.12 Testing with unittest

`rkd.api.testing` provides methods for running tasks with output capturing, a well as mocking RKD classes for unit testing of your task methods. To use our API just extend one of base classes.

7.5.12.1 Example: Running a task on a fully featured RKD executor

```
#!/usr/bin/env python3

import os
from rkd.api.testing import FunctionalTestCase
```

(continues on next page)

(continued from previous page)

```

SCRIPT_DIR_PATH = os.path.dirname(os.path.realpath(__file__))

class TestFunctional(FunctionalTestingCase):
    """
    Functional tests case of the whole application.
    Runs application like from the shell, captures output and performs assertions on
    ↪the results.
    """

    def test_tasks_listing(self):
        """ :tasks """

        full_output, exit_code = self.run_and_capture_output([':tasks'])

        self.assertIn('>> Executing :tasks', full_output)
        self.assertIn('[global]', full_output)
        self.assertIn(':version', full_output)
        self.assertIn('succeed.', full_output)
        self.assertEqual(0, exit_code)

```

7.5.12.2 Example: Mocking RKD-specific dependencies in TaskInterface

```

from rkd.api.inputoutput import BufferedSystemIO
from rkd.api.testing import FunctionalTestingCase

# ...

class SomeTestCase(FunctionalTestingCase):

    # ...

    def test_something_important(self):
        task = LineInFileTask() # put your task class there
        io = BufferedSystemIO()

        BasicTestingCase.satisfy_task_dependencies(task, io=io)

        self.assertEqual('something', task.some_method())

```

7.5.12.3 Documentation

class rkd.api.testing.**BasicTestingCase** (*methodName='runTest'*)

Provides minimum of:

- Doing backup of environment and cwd
- Methods for mocking task dependencies (RKD-specific like ExecutionContext)

environment (*environ: dict*)

Mocks environment

Example usage:

```
with self.environment({'RKD_PATH': SCRIPT_DIR_PATH + './docs/examples/env-in-yaml/rkd'}):  
    ...
```

Parameters `environ` –

Returns

```
static mock_execution_context (task: rkd.api.contract.TaskInterface, args: Dict[str, str] =  
                                None, env: Dict[str, str] = None, defined_args: Dict[str,  
                                dict] = None) → rkd.api.contract.ExecutionContext
```

Prepares a simplified `rkd.api.contract.ExecutionContext` instance

Parameters

- `task` –
- `args` –
- `env` –
- `defined_args` –

Returns

```
static satisfy_task_dependencies (task: rkd.api.contract.TaskInterface,  
                                   io: rkd.api.inputoutput.IO = None) →  
                                   rkd.api.contract.TaskInterface
```

Inserts required dependencies to your task that implements `rkd.api.contract.TaskInterface`

Parameters

- `task` –
- `io` –

Returns

```
setUp () → None
```

Hook method for setting up the test fixture before exercising it.

```
tearDown () → None
```

Hook method for deconstructing the test fixture after testing it.

```
class rkd.api.testing.FunctionalTestingCase (methodName='runTest')
```

Provides methods for running RKD task or multiple tasks with output and exit code capturing. Inherits `Output-CapturingSafeTestCase`.

```
execute_mocked_task_and_get_output (task: rkd.api.contract.TaskInterface, args=None,  
                                     env=None) → str
```

Run a single task, capturing its output in a simplified way. There is no whole RKD bootstrapped in this operation.

Parameters

- `task` (`TaskInterface`) –
- `args` (`dict`) –
- `env` (`dict`) –

Returns

```
run_and_capture_output (argv: list, verbose: bool = False) → Tuple[str, int]
```

Run task(s) and capture output + exit code. Whole RKD from scratch will be bootstrapped there.

Example usage: `full_output, exit_code = self.run_and_capture_output([':tasks'])`

Parameters

- **argv** (*list*) – List of tasks, arguments, commandline switches
- **verbose** (*bool*) – Print all output also to stdout

Returns

class `rkd.api.testing.OutputCapturingSafeTestCase` (*methodName='runTest'*)

Provides hooks for keeping stdout/stderr immutable between tests.

setUp () → None

Hook method for setting up the test fixture before exercising it.

tearDown () → None

Hook method for deconstructing the test fixture after testing it.

7.6 Built-in tasks

7.6.1 Shell

Provides tasks for shell commands execution - mostly used in YAML syntax and in Python modules.

7.6.1.1 :sh

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib.shell</code>	<code>rkd.standardlib.shell</code>	<code>pip install rkd== LECT VERSION</code>	

Executes a Bash script. Can be multi-line.

Notice: phrase %RKD% is replaced with an rkd binary name

Example of plain usage:

```
rkd :sh -c "ps aux"
rkd :sh --background -c "some-heavy-task"
```

Example of task alias usage:

```
from rkd.api.syntax import TaskAliasDeclaration as Task

#
# Example of Makefile-like syntax
#

IMPORTS = []

TASKS = [
    Task(':find-images', [
        ':sh', '-c', 'find ../../ -name \'*.png\''
    ]),
```

(continues on next page)

(continued from previous page)

```

Task(':build', [':sh', '-c', ''' set -x;
    cd ../../../../

    chmod +x setup.py
    ./setup.py build

    ls -la
''']),

# https://github.com/riotkit-org/riotkit-do/issues/43
Task(':hello', [':sh', '-c', 'echo "Hello world"']),
Task(':alias-in-alias-test', [':hello'])
]

```

7.6.1.2 :exec

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib.shell	rkd.standardlib.shell	pip install rkdo==CSEman LECT VERSION	

Works identically as `:sh`, but for spawns a single process. Does not allow a multi-line script syntax.

7.6.1.3 Class to import: BaseShellCommandWithArgumentParsingTask

Creates a command that executes bash script and provides argument parsing using Python's `argparse`. Parsed arguments are registered as `ARG_{{argument_name}}` eg. `--activity-type` would be exported as `ARG_ACTIVITY_TYPE`.

```

IMPORTS += [
    BaseShellCommandWithArgumentParsingTask(
        name=":protest",
        group=":activism",
        description="Take action!",
        arguments_definition=lambda argparse: (
            argparse.add_argument('--activity-type', '-t', help='Select an activity_
↪type')
        ),
        command='''
            echo "Let's act! Let's ${ARG_ACTIVITY_TYPE}!"
            '''
    )
]

```

7.6.2 Technical/Core

7.6.2.1 :init

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib</code>	<code>rkd.standardlib</code>	<code>pip install rkd== SELECT VERSION</code>	

This task runs ALWAYS. `:init` implements a possibility to inherit global settings to other tasks

7.6.2.2 :tasks

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib</code>	<code>rkd.standardlib</code>	<code>pip install rkd== SELECT VERSION</code>	

Lists all tasks that are loaded by all chained `makefile.py` configurations.

Environment variables:

- `RKD_WHITELIST_GROUPS`: (Optional) Comma separated list of groups to only show on the list
- `RKD_ALIAS_GROUPS`: (Optional) Comma separated list of groups aliases eg. “`:international-workers-association->:iwa,:anarchist-federation->:fa`”

7.6.2.3 :version

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib</code>	<code>rkd.standardlib</code>	<code>pip install rkd== SELECT VERSION</code>	

Shows version of RKD and lists versions of all loaded tasks, even those that are provided not by RiotKit. The version strings are taken from Python modules as RKD strongly rely on Python Packaging.

7.6.2.4 CallableTask

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib</code>	<code>rkd.standardlib</code>	<code>pip install rkd== SELECT VERSION</code>	

This is actually not a task to use directly, it is a template of a task to implement yourself. It's kind of a shortcut to create a task by defining a simple method as a callback.

```

import os
from rkd.api.syntax import TaskDeclaration
from rkd.api.contract import ExecutionContext
from rkd.standardlib import CallableTask

def union_method(context: ExecutionContext) -> bool:
    os.system('xdg-open https://iwa-ait.org')
    return True

IMPORTS = [
    TaskDeclaration(CallableTask(':create-union', union_method))
]

TASKS = []

```

class `rkd.standardlib.CallableTask` (*name: str, callback: Callable[[rkd.api.contract.ExecutionContext, rkd.api.contract.TaskInterface], bool], args_callback: Callable[[argparse.ArgumentParser], None] = None, description: str = "", group: str = "", become: str = "", arg_parse_options: List[rkd.api.contract.ArgparseArgument] = None*)

Executes a custom callback - allows to quickly define a short task

configure_argparse (*parser: argparse.ArgumentParser*)

Allows a task to configure ArgumentParser (argparse)

execute (*context: rkd.api.contract.ExecutionContext*) → bool

Executes a task. True/False should be returned as return

get_become_as () → str

User name in UNIX/Linux system, optional. When defined, then current task will be executed as this user (WARNING: a forked process would be started)

get_declared_envs () → Dict[str, str]

Dictionary of allowed envs to override: KEY -> DEFAULT VALUE

get_group_name () → str

Group name where the task belongs eg. “:publishing”, can be empty.

get_name () → str

Task name eg. “:sh”

7.6.2.5 :rkd:create-structure

Package to import	Single task to import	PIP package to install	Stable version
<code>rkd.standardlib</code>	<code>rkd.standardlib</code>	<code>pip install rkd==SE-LECT VERSION</code>	

Creates a template structure used by RKD in current directory.

API for developers:

This task is extensible by class inheritance, you can override methods to implement your own task with changed behavior. It was designed to allow to create customized installers for tools based on RKD (custom RKD distributions), the example is RiotKit Harbor.

Look for “interface methods” in class code, those methods are guaranteed to not change from minor version to minor version.

class `rkd.standardlib.CreateStructureTask`

Creates a RKD file structure in current directory

This task is designed to be extended, see methods marked as “interface methods”.

configure_argparse (*parser: argparse.ArgumentParser*)

Allows a task to configure ArgumentParser (argparse)

execute (*ctx: rkd.api.contract.ExecutionContext*) → bool

Executes a task. True/False should be returned as return

get_group_name () → str

Group name where the task belongs eg. “:publishing”, can be empty.

get_name () → str

Task name eg. “:sh”

get_patterns_to_add_to_gitignore (*ctx: rkd.api.contract.ExecutionContext*) → list

List of patterns to write to .gitignore

Interface method: to be overridden

on_creating_venv (*ctx: rkd.api.contract.ExecutionContext*) → None

When creating virtual environment

Interface method: to be overridden

on_files_copy (*ctx: rkd.api.contract.ExecutionContext*) → None

When files are copied

Interface method: to be overridden

on_git_add (*ctx: rkd.api.contract.ExecutionContext*) → None

Action on, when adding files via *git add*

Interface method: to be overridden

on_requirements_txt_write (*ctx: rkd.api.contract.ExecutionContext*) → None

After requirements.txt file is written

Interface method: to be overridden

on_startup (*ctx: rkd.api.contract.ExecutionContext*) → None

When the command is triggered, and the git is not dirty

Interface method: to be overridden

print_success_msg (*use_pipenv: bool, ctx: rkd.api.contract.ExecutionContext*) → None

Emits a success message

Interface method: to be overridden

7.6.2.6 :file:line-in-file

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib	rkd.standardlib	pipInstallTask== SELECT VERSION	

Similar to the Ansible's lineinfile, replaces/creates/deletes a line in file.

Example usage:

```
echo "Number: 10" > test.txt

rkd -rl debug :file:line-in-file test.txt --regexp="Number: ([0-9]+)?(.*)" --insert=
↪'Number: $match[0] / new: 10'
cat test.txt

rkd -rl debug :file:line-in-file test.txt --regexp="Number: ([0-9]+)?(.*)" --insert=
↪'Number: $match[0] / new: 6'
cat test.txt

rkd -rl debug :file:line-in-file test.txt --regexp="Number: ([0-9]+)?(.*)" --insert=
↪'Number: 50'
cat test.txt

rkd -rl debug :file:line-in-file test.txt --regexp="Number: ([0-9]+)?(.*)" --insert=
↪'Number: $match[0] / new: 90'
cat test.txt
```

7.6.3 Python

This package was extracted from standardlib to rkd_python, but is maintained together with RKD as part of RKD core.

Set of Python-related tasks for building, testing and publishing Python packages.

```
(.venv) riotkit > rkd :py:clean :py:build
>> Executing :py:clean
+ rm -rf pbr.egg.info .eggs dist build

The task ":py:clean" succeed.
-----

>> Executing :py:build
running sdist
[pbr] Writing ChangeLog
[pbr] Generating ChangeLog
[pbr] ChangeLog complete (0.0s)
[pbr] Generating AUTHORS
[pbr] AUTHORS complete (0.0s)
running egg_info
writing src/rkd.egg-info/PKG-INFO
writing dependency_links to src/rkd.egg-info/dependency_links.txt
writing entry points to src/rkd.egg-info/entry_points.txt
writing requirements to src/rkd.egg-info/requires.txt
writing top-level names to src/rkd.egg-info/top_level.txt
writing pbr to src/rkd.egg-info/pbr.json
[pbr] Processing SOURCES.txt
[pbr] In git context, generating filelist from git
warning: no previously-included files found matching '.gitignore'
warning: no previously-included files found matching '.gitreview'
warning: no previously-included files matching '*.pyc' found anywhere in distribution
writing manifest file 'src/rkd.egg-info/SOURCES.txt'
[pbr] reno was not found or is too old. Skipping release notes
```

7.6.3.1 :py:publish

Package to import	Single task to import	PIP package to install	Stable version
rkd_python	rkd_python.PubliTask	pipTask install rkd_python== SE-LECT VERSION	

Publish a package to the PyPI.

Example of usage:

```
rkd :py:publish --username=__token__ --password=... --skip-existing --test
```

7.6.3.2 :py:build

Package to import	Single task to import	PIP package to install	Stable version
rkd_python	rkd_python.BuildTask	pipTask install rkd_python== SE-LECT VERSION	

Runs a build through setuptools.

7.6.3.3 :py:install

Package to import	Single task to import	PIP package to install	Stable version
rkd_python	rkd_python.InstallTask	pip install rkd_python== SELECT VERSION	

Installs the project as Python package using setuptools. Calls ./setup.py install.

7.6.3.4 :py:clean

Package to import	Single task to import	PIP package to install	Stable version
rkd_python	rkd_python.CleanTask	pip install rkd_python== SELECT VERSION	

Removes all files related to building the application.

7.6.3.5 :py:unittest

Package to import	Single task to import	PIP package to install	Stable version
rkd_python	rkd_python.UnitTestTask	pip install rkd_python== SELECT VERSION	

Runs Python's built-in unittest module to execute unit tests.

Examples:

```
rkd :py:unittest
rkd :py:unittest -p some_test
rkd :py:unittest --tests-dir=./test
```

7.6.4 ENV

Manipulates the environment variables stored in a .env file

RKD is always loading an .env file on startup, those tasks in this package allows to manage variables stored in .env file in the scope of a project.

7.6.4.1 :env:get

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib.env	rkd.standardlib.env.InstallTask	pip install rkd== SELECT VERSION	

Example of usage:

```
rkd :env:get --name COMPOSE_PROJECT_NAME
```

7.6.4.2 :env:set

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib.env	rkd.standardlib	pip install rkd== SELECT VERSION	

Example of usage:

```
rkd :env:set --name COMPOSE_PROJECT_NAME --value hello
rkd :env:set --name COMPOSE_PROJECT_NAME --ask
rkd :env:set --name COMPOSE_PROJECT_NAME --ask --ask-text="Please enter your name:"
```

7.6.5 JINJA

Renders JINJA2 files, and whole directories of files. Allows to render by pattern.

All includes and extends are by default looking in current working directory path.

7.6.5.1 :j2:render

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib.jinja	rkd.standardlib	pip install rkd== SELECT VERSION	

Renders a single file from JINJA2.

Example of usage:

```
rkd :j2:render -s SOURCE-FILE.yaml.j2 -o OUTPUT-FILE.yaml
```

7.6.5.2 :j2:directory-to-directory

Package to import	Single task to import	PIP package to install	Stable version
rkd.standardlib.jinja	rkd.standardlib	pip install rkd== SELECT VERSION	

Renders all files recursively in given directory to other directory. Can remove source files after rendering them to the output files.

Note: Pattern is a regexp pattern that matches whole path, not only file name

Note: Exclude pattern is matching on SOURCE files, not on target files

Example usage:

```
rkd :j2:directory-to-directory \  
  --source="/some/path/templates" \  
  --target="/some/path/rendered" \  
  --delete-source-files \  
  --pattern="(.*).j2"
```

A

ask() (*rkd.api.inputoutput.Wizard method*), 38
 assign_temporary_file() (*rkd.api.temp.TempManager method*), 33

B

BasicTestingCase (*class in rkd.api.testing*), 34, 41

C

CallableTask (*class in rkd.standardlib*), 46
 capture_descriptors() (*rkd.api.inputoutput.IO method*), 32
 configure_argparse() (*rkd.api.contract.TaskInterface method*), 29
 configure_argparse() (*rkd.standardlib.CallableTask method*), 46
 configure_argparse() (*rkd.standardlib.CreateStructureTask method*), 47
 copy_internal_dependencies() (*rkd.api.contract.TaskInterface method*), 29
 CreateStructureTask (*class in rkd.standardlib*), 47
 critical() (*rkd.api.inputoutput.IO method*), 32

D

debug() (*rkd.api.inputoutput.IO method*), 32

E

environment() (*rkd.api.testing.BasicTestingCase method*), 34, 41
 err() (*rkd.api.inputoutput.IO method*), 32
 errln() (*rkd.api.inputoutput.IO method*), 32
 error() (*rkd.api.inputoutput.IO method*), 32
 error_msg() (*rkd.api.inputoutput.IO method*), 32
 exec() (*rkd.api.contract.TaskInterface method*), 30
 execute() (*rkd.api.contract.TaskInterface method*), 30

execute() (*rkd.standardlib.CallableTask method*), 46
 execute() (*rkd.standardlib.CreateStructureTask method*), 47
 execute_mocked_task_and_get_output() (*rkd.api.testing.FunctionalTestingCase method*), 35, 42
 ExecutionContext (*class in rkd.api.contract*), 31

F

finally_clean_up() (*rkd.api.temp.TempManager method*), 33
 find_path_by_name() (*rkd.yaml_parser.YamlFileLoader method*), 36
 finish() (*rkd.api.inputoutput.Wizard method*), 38
 format_task_name() (*rkd.api.contract.TaskInterface method*), 30
 FunctionalTestingCase (*class in rkd.api.testing*), 34, 42

G

get_arg() (*rkd.api.contract.ExecutionContext method*), 31
 get_arg_or_env() (*rkd.api.contract.ExecutionContext method*), 31
 get_become_as() (*rkd.api.contract.TaskInterface method*), 30
 get_become_as() (*rkd.standardlib.CallableTask method*), 46
 get_declared_envs() (*rkd.api.contract.TaskInterface method*), 30
 get_declared_envs() (*rkd.standardlib.CallableTask method*), 46
 get_env() (*rkd.api.contract.ExecutionContext method*), 32
 get_full_name() (*rkd.api.contract.TaskInterface method*), 30

get_group_name() (*rkd.api.contract.TaskInterface method*), 30
 get_group_name() (*rkd.standardlib.CallableTask method*), 46
 get_group_name() (*rkd.standardlib.CreateStructureTask method*), 47
 get_name() (*rkd.api.contract.TaskInterface method*), 30
 get_name() (*rkd.standardlib.CallableTask method*), 46
 get_name() (*rkd.standardlib.CreateStructureTask method*), 47
 get_patterns_to_add_to_gitignore() (*rkd.standardlib.CreateStructureTask method*), 47

H

h1() (*rkd.api.inputoutput.IO method*), 32
 h2() (*rkd.api.inputoutput.IO method*), 32
 h3() (*rkd.api.inputoutput.IO method*), 32
 h4() (*rkd.api.inputoutput.IO method*), 32

I

info() (*rkd.api.inputoutput.IO method*), 33
 info_msg() (*rkd.api.inputoutput.IO method*), 33
 input() (*rkd.api.inputoutput.Wizard method*), 38
 IO (*class in rkd.api.inputoutput*), 32
 io() (*rkd.api.contract.TaskInterface method*), 30
 is_silent() (*rkd.api.inputoutput.IO method*), 33

L

load() (*rkd.yaml_parser.YamlFileLoader method*), 36
 load_from_file() (*rkd.yaml_parser.YamlFileLoader method*), 36
 load_previously_stored_values() (*rkd.api.inputoutput.Wizard method*), 38

M

mock_execution_context() (*rkd.api.testing.BasicTestingCase static method*), 34, 42

O

on_creating_venv() (*rkd.standardlib.CreateStructureTask method*), 47
 on_files_copy() (*rkd.standardlib.CreateStructureTask method*), 47
 on_git_add() (*rkd.standardlib.CreateStructureTask method*), 47
 on_requirements_txt_write() (*rkd.standardlib.CreateStructureTask method*), 47

on_startup() (*rkd.standardlib.CreateStructureTask method*), 47
 opt_out() (*rkd.api.inputoutput.IO method*), 33
 opt_outln() (*rkd.api.inputoutput.IO method*), 33
 opt_in() (*rkd.api.inputoutput.IO method*), 33
 outln() (*rkd.api.inputoutput.IO method*), 33
 OutputCapturingSafeTestCase (*class in rkd.api.testing*), 35, 43

P

print_group() (*rkd.api.inputoutput.IO method*), 33
 print_line() (*rkd.api.inputoutput.IO method*), 33
 print_opt_line() (*rkd.api.inputoutput.IO method*), 33
 print_separator() (*rkd.api.inputoutput.IO method*), 33
 print_success_msg() (*rkd.standardlib.CreateStructureTask method*), 47
 py() (*rkd.api.contract.TaskInterface method*), 30

R

rkd() (*rkd.api.contract.TaskInterface method*), 30
 run_and_capture_output() (*rkd.api.testing.FunctionalTestingCase method*), 35, 42

S

satisfy_task_dependencies() (*rkd.api.testing.BasicTestingCase static method*), 34, 42
 setUp() (*rkd.api.testing.BasicTestingCase method*), 34, 42
 setUp() (*rkd.api.testing.OutputCapturingSafeTestCase method*), 35, 43
 sh() (*rkd.api.contract.TaskInterface method*), 30
 should_fork() (*rkd.api.contract.TaskInterface method*), 30
 silent_sh() (*rkd.api.contract.TaskInterface method*), 30
 success_msg() (*rkd.api.inputoutput.IO method*), 33

T

table() (*rkd.api.contract.TaskInterface static method*), 30
 TaskAliasDeclaration (*class in rkd.api.syntax*), 31
 TaskDeclaration (*class in rkd.api.syntax*), 31
 TaskInterface (*class in rkd.api.contract*), 29
 tearDown() (*rkd.api.testing.BasicTestingCase method*), 34, 42
 tearDown() (*rkd.api.testing.OutputCapturingSafeTestCase method*), 35, 43

TempManager (*class in rkd.api.temp*), 33

W

warn() (*rkd.api.inputoutput.IO method*), 33

Wizard (*class in rkd.api.inputoutput*), 38

Y

YamlFileLoader (*class in rkd.yaml_parser*), 36